

TWINHORN VA-500 VERTICAL MACHINING CENTER

STANDARD FEATURES

- ▶ Fanuc Oi-MC & 640 Meters Memory
- ▶ AC Digital Servo & Spindle Drivers
- ▶ High Precision Contouring Function (AICC)
- ▶ PCMCIA Slot for Memory Expansion
- ▶ Helical Interpolation & Custom Macro B
- ▶ Hardened Ground Box Ways on X,Y & Z
- ▶ Meehanite Cast Iron Bed, Base & Headstock
- ▶ Heat Exchanger for Electrical Cabinet
- ▶ Automatic Power off (M30)
- ▶ Roll Out Coolant Tank & Chip Tray
- ▶ Operating & Electrical Manuals
- ▶ One Year Machine Parts Warranty
- ▶ Fanuc 10 HP Spindle Motor
- ▶ Spindle CAT-40 with 8000 RPM
- ▶ Arm Type 16 Tool ATC
- ▶ RS232 Interface
- ▶ Pitch Error Compensation
- ▶ Auto Lubrication System
- ▶ Fully Enclosed Splash Guard
- ▶ Spindle Air Blast & Cutting Air Blast
- ▶ Spindle Air Curtain
- ▶ Tool Kit / Work Light
- ▶ Hand Held Air Nozzle
- ▶ Two Year Control Warranty

MACHINE SPECIFICATIONS

| | |
|---|-------------------------------------|
| Travel X Axis ----- | 19.69" (500mm) |
| Travel Y Axis ----- | 15.75" (400mm) |
| Travel Z Axis ----- | 17.72" (450mm) |
| Rapid Feed Rate X & Y Axis ----- | 787ipm |
| Rapid Feed Rate Z Axis ----- | 630ipm |
| Cutting Feed Rate ----- | 196.85ipm (5000mm/min) |
| Positioning X, Y & Z Axis ----- | 0.0001/12" (0.005mm/300mm) |
| Repeatability X, Y & Z Axis ----- | ±0.0001" (±0.003mm) |
| Table Dimension ----- | 27.56" x 15.75" (700mm x 400mm) |
| Maximum Loading ----- | 660 lb (300Kg) |
| Spindle Motor ----- | FANUC AC Spindle Motor β 6 / 10000i |
| Spindle Horse Power ----- | 10 hp |
| Spindle Speed ----- | 8000 RPM |
| Spindle Taper ----- | CAT- 40 |
| Servo Drive Motor X & Y Axis ----- | Fanuc β 8 / 3000is |
| Servo Drive Motor Z Axis ----- | Fanuc β 12 / 3000is |
| Distance from Spindle Nose to Table ----- | 4.72" – 22.44" (120 – 570mm) |
| Distance from Spindle to Column ----- | 18.90" (480mm) |

Note: Prices and model specifications are subject to change without prior notice. All prices are in U.S. Dollars.

September 1, 2006

| | |
|-----------------------------|--|
| ATC ----- | Swing Arm Type Random, Shortest Path, Bi-Directional |
| Magazine Capacity ----- | 16 Tools |
| Tool Change Time ----- | 2.5 Second |
| Maximum Tool Weight ----- | 15.4 lb (7.0kg) |
| Maximum Tool Length ----- | 11.81" (300mm) |
| Maximum Tool Diameter ----- | 3.14" (80mm) |
| Floor Space W x D x H ----- | 77.17"x84.65"x95.47" (1960mmx2150mmx2425mm) |
| Power Requirement ----- | 220V, 3 Phase, 60Hz, 15kVA, 50Amp |
| Machine Weight ----- | 8,360 lb (3800 kg) |

MACHINE PRICES

| | |
|---|-----------------|
| VA-500 Fanuc Oi-MC Control / 8000RPM / 16 Tool Arm Type ATC ----- | \$45,000 |
|---|-----------------|

OPTIONAL ACCESSORIES

| | |
|--|-----------|
| Mitsubishi M64SM Control ----- | N/C |
| Mitsubishi M65SM Control ----- | \$4,500 |
| Fanuc 21i-MB Control ----- | \$10,800 |
| Fanuc 18i-MB Control ----- | \$15,000 |
| Spindle Speed 10,000RPM ----- | \$3,500 |
| Spindle Speed 12,000RPM ----- | \$5,500 |
| Data Server 256MB (DNC) ----- | \$2,300 |
| Spindle Motor 10/15Hp ----- | \$2,200 |
| Geneva Type ATC 16 Tool ----- | (\$3,000) |
| 4 th Axis Interface Included Servo Drive & Power/Signal Cable + Install ----- | \$4,300 |
| 4 th Axis Complete with Manual Tailstock + Install (Tanshing VRNC-125) ----- | \$10,900 |
| Chain Type Chip Conveyor & Cart ----- | \$3,250 |
| Spiral Type Chip Conveyor & Cart ----- | \$1,950 |
| Spindle oil Refrigeration Unit ----- | \$1,700 |
| Coolant Through Spindle (Included Filter System) ----- | \$10,800 |
| Chip Flushing System ----- | \$780 |
| Coolant Ring ----- | \$470 |
| Water Curtain Device ----- | \$590 |
| Oil Skimmer ----- | \$590 |
| Transformer 15KVA ----- | \$1,030 |

Note: Prices and model specifications are subject to change without prior notice. All prices are in U.S. Dollars.

Twinhorn VA-500 Machine Specifications

1. HEADSTOCK

| | | |
|--|-------|-------------------------------|
| A. Belt Drive | ----- | Variable Speed |
| B. Belt Type | ----- | 920-8YU-40W for 60 to 8000Rpm |
| C. Belt Type | ----- | 810-5GT-35W for 12000Rpm |
| D. Spindle Bearings Grade | ----- | P4 |
| Angular Contact (Front) (60-8000Rpm) | ----- | DBD-7013C |
| Angular Contact (Front) (120-12000Rpm) | ----- | HS-7013E*2 |
| Contact Angle | ----- | 15° / 25° (OP) |
| O.D | ----- | 3.937" (100mm) |
| I.D | ----- | 2.559" (65mm) |
| Width | ----- | 0.709" (18mm) |
| Angular Contact (Rear) (60-8000Rpm) | ----- | 6011 |
| Angular Contact (Rear) (120-12000Rpm) | ----- | HS-7011E*2 |
| O.D | ----- | 3.543" (90mm) |
| I.D | ----- | 2.165" (55mm) |
| Width | ----- | 0.709" (18mm) |
| E. Spindle Shaft Hardness | ----- | HRC 60 - 62 |
| F. Retention System | ----- | Bevel Springs 88 pc |
| G. Holding Force | ----- | 1,892 lb (860kg) |
| H. Counter Balance | ----- | Mechanical |
| I. Spindle Orientation | ----- | Sensor |
| J. Spindle Taper | ----- | CT or BT40 |

2. TABLE

| | |
|--------------------|--------------------------------|
| A. Dimensions | |
| Length | ----- 27.56" (700mm) |
| Width | ----- 15.75" (400mm) |
| B. Max. Table Load | ----- 660 lb (300kg) |
| C. Slide Way | ----- Harden & Ground Box Ways |

3. AUTOMATIC TOOL CHANGER (ATC)

| | | |
|---|-------|---|
| A. Type | ----- | Arm Type, Random, Shortest Path, Bi-Directional |
| B. Max Tool Weight | ----- | 15.4 lb (7kg) |
| C. Max Tool Length | ----- | 11.81" (300mm) |
| D. Tool Change Time (Tool to Tool) | ----- | 2.5 Seconds |
| E. Magazine Capacity | ----- | 16 Tools |
| Max Tool Diameter (Adjacent Pot Tooled) | ----- | 3.14" (80mm) |
| Max. Tool Dia. (Adjacent Pot Empty) | ----- | 4.92" (125mm) |

4. X AXIS

| | | |
|--------------------------------------|-------|---|
| A. Ballscrew Diameter | ----- | 1.26" (32mm) |
| Lead | ----- | 0.315" (8mm) |
| Accuracy | ----- | C3 |
| B. Drive Motor | ----- | Fanuc β 8 / 3000is |
| C. Thrust (Continuous) | ----- | 1518 lb (690kg) |
| D. Rapid Rate (Box Way) | ----- | 787ipm (20000mm/min) |
| E. Harden Ground Box Way (L x W x H) | ----- | 43.70" x 2.56" x 1.38" (1110 x 65 x 35mm) |
| F. Travel | ----- | 19.69" (500mm) |
| G. Positioning | ----- | 0.0001"/12" |
| H. Repeatability | ----- | ± 0.0001" |

5. Y AXIS

| | | |
|--------------------------------------|-------|---|
| A. Ballscrew Diameter | ----- | 1.26" (32mm) |
| Lead | ----- | 0.315" (8mm) |
| Accuracy | ----- | C3 |
| B. Drive Motor | ----- | Fanuc β 8 / 3000is |
| C. Thrust (Continuous) | ----- | 1518 lb (690kg) |
| D. Rapid Rate (Box Way) | ----- | 787ipm (20000mm/min) |
| E. Harden Ground Box Way (L x W x H) | ----- | 39.57" x 3.15" x 1.57" (1005 x 80 x 40mm) |
| F. Travel | ----- | 15.75" (400mm) |
| G. Positioning | ----- | 0.0001"/12" |
| H. Repeatability | ----- | ± 0.0001" |

6. Z AXIS

| | | |
|--------------------------------------|-------|---|
| A. Ballscrew Diameter | ----- | 1.26" (32mm) |
| Lead | ----- | 0.315" (8mm) |
| Accuracy | ----- | C3 |
| B. Drive Motor | ----- | Fanuc β 12 / 3000is |
| C. Thrust (Continuous) | ----- | 1518 lb (690kg) |
| D. Rapid Rate | ----- | 630ipm (16000mm/min) |
| E. Harden Ground Box Way (L x W x H) | ----- | 40.16" x 3.54" x 1.57" (1020 x 90 x 40mm) |
| F. Travel | ----- | 17.72" (450mm) |
| G. Positioning | ----- | 0.0001"/12" |
| H. Repeatability | ----- | ± 0.0001" |

Note: Prices and model specifications are subject to change without prior notice. All prices are in U.S. Dollars.



7. COOLANT SYSTEM

- A. Coolant Motor Type ----- MTH2-30
- B. Pump Capacity ----- ½ Hp
- C. Coolant Tank Volume ----- 150L
- D. Coolant Flush System (Option) ----- CH2-30*2

8. FLOOR SPACE REQUIREMENTS

- A. Length ----- 76.97" (1955mm)
- B. Width ----- 90.16" (2290mm)
- C. Height ----- 94.02" (2388mm)

9. PACKING SIZE

- A. Standard Machine ----- T/A

10. WEIGHT

- A. Net ----- 8,360 lb (3800kg)
- B. Gross ----- 8,690 lb (3950kg)

11. POWER REQUIREMENTS

- 220 Volt ----- 208/220 VAC, 3 Phase / 50 Amps
- 440 Volt ----- 220-440 3 Phase Transformer / 15 kVA

Note: Prices and model specifications are subject to change without prior notice. All prices are in U.S. Dollars.

Fanuc 0i-MC (Package B) Standard Features

- * Work piece coordinate system (G52 – G59)
- * Manual absolute on and off
- * Programmable data input (G10)
- * Custom macro B
- * Interruption type custom macro
- * Circular interpolation by R programming
- * Feedrate clamp based on arc radius
- * Programmable mirror image
- * Conversational programming with graphic function (Graphic module is required)
- * <Auxiliary/Spindle speed function>
- * 2nd auxiliary function (B8-digit)
- * High speed M/S/T interface
- * Spindle serial output
- * Spindle override
- * 1st spindle orientation
- * 2nd spindle orientation
- * Spindle synchronous control
- * <Tool function/Tool compensation>
- * Tool offset pairs +-6-digit 400
- * Tool length compensation (G43/G44)
- * Cutter compensation C (G41/G42)
- * Extended tool life management
- * Automatic tool length measurement (G37)
- * Part program storage length 320 m
- * Part program editing
- * Background editing
- * Playback
- * Status display
- * Current position display
- * Parameter setting and display
- * Alarm display
- * Operator message history display
- * Help function
- * Actual cutting speed display
- * Directory display of floppy cassette
- * Spindle setting screen
- * Display of hardware and software configuration
- * Software operator's panel general purpose switch
- * Multi-language display English, Japanese, German/French, Italian, Chinese, Spanish, Korean
- * Direct input of work piece origin offset valve measured
- * Optional chamfering / corner R
- * Sub program call (4 folds)
- * Pattern data input
- * Canned cycle for drilling
- * Automatic corner deceleration
- * Coordinate system rotation
- * Tape format for FS10/11
- * Auxiliary function (M8-digit)
- * Auxiliary function lock
- * Multiple command of auxiliary function
- * Spindle analog output
- * Analog voltage control by PMC
- * 1st spindle output switching function
- * 2nd spindle output switching function
- * Rigid tapping
- * Tool function (T8-digit)
- * Tool offset memory C
- * Tool offset (G45~G48)
- * Tool life management
- * Tool length measurement
- * <Editing operation>
- * Number of registerable programs 400
- * Program protect
- * Extended part program editing
- * <Setting and display>
- * Clock function
- * Program display
- * Self-diagnosis function
- * Alarm history display
- * Operation history display
- * Run hour and parts count display
- * Display of spindle speed and T-code
- * Servo setting screen
- * Servo waveform display (Graphic module is required)
- * Software operator's panel
- * Data protection key

- * Erase display
- * Reader/puncher interface (2 ch)
- * External tool offset
- * External machine zero point shift
- * External key input
- * External work piece number search
- * Power Mate CNC manager
- * <Others>
- * CNC screen display
- * <Controlled axis>
- * Simultaneous controllable axes; 4
- * Axis name (X, Y, Z, U, V, W, A, B, C)
- * Least input increment (0.001 mm, 0.001 deg, 0.001 inch)
- * Incremental system 1/10
- * Fine Acc & Dec control
- * Inch/metric conversion
- * Machine lock
- * Overtravel
- * Stroke limit external setting
- * Mirror image
- * Servo-off/mechanical handle
- * Backlash compensation for each rapid traverse and cutting feed
- * Stored pitch error compensation
- * Unexpected disturbance torque detection function
- * <Operation>
- * DNC operation
- * Schedule function
- * Sequence number search
- * Program restart
- * Retraction for rigid tapping
- * Dry run
- * JOG feed
- * Reference position return without DOG
- * Reference position shift
- * Manual handle feed rate
- * Incremental feed
- * <Interpolation functions>
- * Linear interpolation type positioning
- * Exact stop mode (G61)
- * Linear interpolation (G01)
- * <Data input/output>
- * External I/O device control
- * External message
- * External data input
- * External program input
- * External program number search
- * Memory card interface for maintenance
- * Status output signal
- * Built-in Ethernet
- * Number of controlled axes; 4
- * Axis control by PMC
- * Simple synchronous control
- * Flexible feed gear
- * HRV control
- * Interlock
- * Emergency stop
- * Stored stroke check 1
- * Stored stroke check 2
- * Follow-up
- * Backlash compensation
- * Position switch
- * Control axis detach
- * Automatic operation (memory)
- * MDI operation
- * Program number search
- * Sequence number comparison and stop
- * Manual intervention and return
- * Buffer register
- * Single block
- * Manual reference position return
- * Reference position setting with mechanical stopper
- * Manual handle feed
- * Manual handle interruption
- * Jog and handle simultaneous mode
- * Positioning (G00)
- * Single direction positioning
- * Exact stop (G09)
- * Circular interpolation (G02/G03)

- * Dwell (G04)
- * Helical interpolation
- * Skip (G31)
- * Reference position return (G28)
- * 2nd reference position return
- * Normal direction control
- * <Feed function>
- * Rapid traverse override
- * Feed per revolution
- * Cutting federate clamp
- * Rapid traverse bell shaped acceleration/deceleration
- * Linear acceleration/deceleration after cutting feed interpolation
- * Bell-shaped acc/dec after cutting feed interpolation
- * Feedrate override
- * Jog override
- * External deceleration
- * <Program input>
- * Label skip
- * Control in/out
- * Max. programmable dimension +- 8-digit
- * Sequence number
- * Decimal point programming/pocket calculator type decimal point programming
- * Input unit 10 time multiply
- * Rotary axis designation
- * Polar coordinate command
- * Automatic coordinate system setting
- * Cylindrical interpolation
- * Threading/synchronous cutting
- * High-speed skip
- * Reference position return check (G27)
- * 3rd/4th reference position return
- * Index table indexing
- * Rapid traverse rate; 240m/min (1 m)
- * Feed per minute
- * Tangential speed control
- * Automatic acceleration/deceleration
- * One digit F-code feed
- * Override cancel
- * Advanced preview control
- * Tape cede EIA; RS244/ISO840
- * Parity check
- * Optional block skip
- * Program number
- * Absolute/incremental command
- * Plane selection (G17, G18, G19)
- * Rotary axis roll-over
- * Coordinate system setting (G92)