

## TWINHORN VH-1010 VERTICAL MACHINING CENTER

### STANDARD FEATURES

- ▶ Fanuc Oi-MC & 640 Meters Memory
- ▶ AC Digital Servo & Spindle Drivers
- ▶ High Precision Contouring Function (AICC)
- ▶ PCMCIA Slot for Memory Expansion
- ▶ Helical Interpolation & Custom Macro B
- ▶ Hardened Ground Box Ways on X,Y & Z
- ▶ Meehanite Cast Iron Bed, Base & Headstock
- ▶ Heat Exchanger for Electrical Cabinet
- ▶ Automatic Power off (M30)
- ▶ Roll Out Coolant Tank & Chip Tray
- ▶ Fanuc Operating & Maintenance Manual
- ▶ 4<sup>th</sup> Axis Interface Cable only Ready
- ▶ One Year Machine Parts Warranty
- ▶ Fanuc 15 HP Spindle Motor
- ▶ Spindle CAT-40 with 8000 RPM
- ▶ Arm Type 24 Tool ATC
- ▶ RS232 Interface
- ▶ Pitch Error Compensation
- ▶ Auto Lubrication System
- ▶ Fully Enclosed Splash Guard
- ▶ Spindle Air Blast & Cutting Air Blast
- ▶ Spindle Air Curtain
- ▶ Tool Kit / Work Light
- ▶ Operating & Electrical Manuals
- ▶ Hand Held Coolant & Air Nozzle
- ▶ Two Year Control Warranty

### MACHINE SPECIFICATIONS

Travel X Axis -----	39.76" (1010mm)
Travel Y Axis -----	19.69" (500mm)
Travel Z Axis -----	20.47" (520mm)
Rapid Feed Rate X & Y Axis -----	630ipm
Rapid Feed Rate Z Axis -----	630ipm
Cutting Feed Rate -----	196.85ipm (5000mm/min)
Positioning X, Y & Z Axis -----	0.0001/12" (0.005mm / 300mm)
Repeatability X, Y & Z Axis -----	±0.0001" (±0.003mm)
Table Dimension -----	47.24" x 17.72" (1200mm x 450mm)
Maximum Loading -----	990 lb (450Kg)
Spindle Motor -----	FANUC AC Spindle Motor βiI 8 / 8000
Spindle Horse Power -----	15 HP
Spindle Speed -----	8000 RPM
Spindle Taper -----	CAT-40
Servo Drive Motor X & Y Axis -----	Fanuc β 12 / 3000is
Servo Drive Motor Z Axis -----	Fanuc β 22 / 3000is
Distance from Spindle Nose to Table -----	4.72" – 25.59" (120 – 650mm)
Distance from Spindle to Column -----	21.26" (540mm)

Note: Prices and model specifications are subject to change without prior notice. All prices are in U.S. Dollars.

September 1, 2006

ATC -----	Swing Arm Type Random, Shortest Path, Bi-Directional
Magazine Capacity -----	24 Tools
Tool Change Time -----	2.5 Second
Maximum Tool Weight -----	15.4 lb (7.0kg)
Maximum Tool Length -----	11.81" (300mm)
Maximum Tool Diameter -----	3.14" (80mm)
Floor Space L x W x H -----	99"x115"x106" (2508mmx2900mmx2700mm)
Power Requirement -----	220V, 3 Phase, 60Hz, 30kVA, 75Amp
Machine Weight -----	11,770 lb (5350 kg)

**MACHINE PRICES**

VH-1010 Fanuc Oi-MC Control / 8000RPM / 24 Tool Arm Type ATC -----	<b>\$69,900</b>
--	-----------------

**OPTIONAL ACCESSORIES**

Mitsubishi 64SM Control -----	N/C
Mitsubishi 65SM Control -----	\$5,800
Fanuc 21i-MC Control -----	\$10,000
Fanuc 18i-MC Control -----	\$15,000
Spindle Speed 10,000RPM -----	\$3,500
Spindle Speed 12000RPM -----	\$5,500
Spindle Motor 20 Hp -----	\$3,600
Data Server 256MB (DNC) -----	\$2,300
Spiral Type Chip Conveyor & Cart -----	\$1,950
Chain Type Chip Conveyor & Cart -----	\$3,250
Spindle Oil Refrigeration Unit -----	\$1,700
Coolant Through Spindle (Included Filter System) -----	\$10,800
Coolant Through Tool -----	\$1,250
Chip Flushing System -----	\$780
Coolant Ring -----	\$470
Water Curtain Device -----	\$590
Oil Skimmer -----	\$590
ZF Gearbox -----	\$8,450
4 <sup>th</sup> Axis Interface with Servo Drive & Power/Signal Cable -----	\$4,300
4 <sup>th</sup> Axis Complete with Manual Tailstock + Install (Tanshing VRNC-210) -----	\$14,800
4 <sup>th</sup> Axis Complete with Manual Tailstock + Install (Golden Sun CNC-251R) -----	\$15,000
Transformer 25KVA -----	\$1,200

Note: Prices and model specifications are subject to change without prior notice. All prices are in U.S. Dollars.

## Twinhorn VH-1010 Machine Specifications

### 1. HEADSTOCK

A. Belt Drive	-----	Variable Speed
B. Belt Type	-----	920-8YU-40W for 6000 to 8000Rpm
C. Belt Type	-----	810-5GT-35W for 12000Rpm
D. Spindle Bearings Grade (8000 RPM)	-----	P4
Angular Contact (Front)	-----	7013C DBD P4
Contact Angle	-----	15 Degrees
O.D	-----	3.937" (100mm)
I.D	-----	2.559" (65mm)
Width	-----	0.709" (18mm)
Angular Contact (Rear)	-----	6011
O.D	-----	3.543" (90mm)
I.D	-----	2.165" (55mm)
Width	-----	0.709" (18mm)
E. Spindle Shaft Hardness	-----	HRC 60 - 62
F. Retention System	-----	Bevel Springs 88 pc
G. Holding Force	-----	1,892 lb (860kg)
H. Counter Balance	-----	Mechanical
I. Spindle Orientation	-----	Sensor
J. Spindle Taper	-----	CT or BT40
K. Spindle Motor	-----	Fanuc B12/7000i (7.5 / 11 Kw) 10 / 15 Hp

### 2. TABLE

A. Dimensions	
Length	----- 47.24" (1200mm)
Width	----- 17.72" (450mm)
B. Max. Table Load	----- 990 lb (450kg)
C. Slideways	----- Hardened & Ground Box Ways

### 3. AUTOMATIC TOOL CHANGER (ATC)

A. Type	-----	Arm Type Random, Shortest Path, Bi-Directional
B. Max. Tool Weight	-----	15.4 lb (7kg)
C. Max. Tool Length	-----	11.81" (300mm)
D. Tool Change Time (Tool to Tool)	-----	2.5 Seconds
E. Magazine Capacity	-----	24 Tools
Max. Tool Dia. (Adjacent Pot Tooled)	-----	3.14" (80mm)
Max. Tool Dia. (Adjacent Pot Empty)	-----	4.92" (125mm)

Note: Prices and model specifications are subject to change without prior notice. All prices are in U.S. Dollars.

**4. X AXIS**

A. Ballscrew Diameter	-----	1.57" (40mm)
Lead	-----	0.393" (10mm)
Accuracy	-----	C3
B. Drive Motor	-----	Fanuc B12/3000i Motor
C. Thrust ( <b>Continuous</b> )	-----	1518 lb (690kg)
D. Rapid Rate	-----	630ipm (16000mm/min)
E. Harden Ground Box Way (L x W x H)	-----	78.74" x 2.95" x 1.38" (2000 x 75 x 35mm)
F. Travel	-----	39.76" (1010mm)
G. Positioning	-----	0.0001"/12"
H. Repeatability	-----	± 0.0001"

**5. Y AXIS**

A. Ballscrew Diameter	-----	1.57" (40mm)
Lead	-----	0.393" (10mm)
Accuracy	-----	C3
B. Drive Motor	-----	Fanuc B12/3000i Motor
C. Thrust ( <b>Continuous</b> )	-----	1518 lb (690kg)
D. Rapid Rate	-----	630ipm (16000mm/min)
E. Harden Ground Box Way (L x W x H)	-----	44.06" x 3.94" x 1.57" (1119 x 100 x 40mm)
F. Travel	-----	19.69" (500mm)
G. Positioning	-----	0.0001"/12"
H. Repeatability	-----	± 0.0001"

**6. Z AXIS**

A. Ballscrew Diameter	-----	1.57" (40mm)
Lead	-----	0.393" (10mm)
Accuracy	-----	C3
B. Drive Motor	-----	Fanuc B22 Motor
C. Thrust ( <b>Continuous</b> )	-----	1518 lb (690kg)
D. Rapid Rate	-----	630ipm (16000mm/min)
E. Harden Ground Box Way (L x W x H)	-----	43.85" x 2.95" x 1.57" (1114 x 75 x 40mm)
F. Travel	-----	20.47" (520mm)
G. Positioning	-----	0.0001"/12"
H. Repeatability	-----	± 0.0001"

Note: Prices and model specifications are subject to change without prior notice. All prices are in U.S. Dollars.

**7. COOLANT SYSTEM**

- A. Coolant Motor Type ----- CH2-30 / 780W-60HZ
- B. Pump Capacity ----- 33.3 L / min-0.3bar
- C. Coolant Tank Volume ----- 200L
- D. Coolant Flush System (Option) ----- CH2-30\*2

**8. FLOOR SPACE REQUIREMENTS**

- A. Length ----- 98.74" (2508mm)
- B. Width ----- 114.17" (2900mm)
- C. Height ----- 106.30" (2700mm)

**9. PACKING SIZE**

- A. Standard Machine ----- 109.76" x 90.55" x 96.46" (2788 x 2300 x 2450mm)

**10. WEIGHT**

- A. Net ----- 11,770 lb (5350kg)

**11. POWER REQUIREMENTS**

- 220 Volt ----- 208/220 VAC, 3 Phase / 75 Amps
- 440 Volt ----- 220-440 3 Phase Transformer / 30 kVA

Note: Prices and model specifications are subject to change without prior notice. All prices are in U.S. Dollars.

### Fanuc 0i-MC (Package B) Standard Features

- \* Work piece coordinate system (G52 – G59)
- \* Manual absolute on and off
- \* Programmable data input (G10)
- \* Custom macro B
- \* Interruption type custom macro
- \* Circular interpolation by R programming
- \* Feedrate clamp based on arc radius
- \* Programmable mirror image
- \* Conversational programming with graphic function (Graphic module is required)
- \* <Auxiliary/Spindle speed function>
- \* 2<sup>nd</sup> auxiliary function (B8-digit)
- \* High speed M/S/T interface
- \* Spindle serial output
- \* Spindle override
- \* 1<sup>st</sup> spindle orientation
- \* 2<sup>nd</sup> spindle orientation
- \* Spindle synchronous control
- \* <Tool function/Tool compensation>
- \* Tool offset pairs +-6-digit 400
- \* Tool length compensation (G43/G44)
- \* Cutter compensation C (G41/G42)
- \* Extended tool life management
- \* Automatic tool length measurement (G37)
- \* Part program storage length 320 m
- \* Part program editing
- \* Background editing
- \* Playback
- \* Status display
- \* Current position display
- \* Parameter setting and display
- \* Alarm display
- \* Operator message history display
- \* Help function
- \* Actual cutting speed display
- \* Directory display of floppy cassette
- \* Spindle setting screen
- \* Display of hardware and software configuration
- \* Software operator's panel general purpose switch
- \* Multi-language display English, Japanese, German/French, Italian, Chinese, Spanish, Korean
- \* Direct input of work piece origin offset valve measured
- \* Optional chamfering / corner R
- \* Sub program call (4 folds)
- \* Pattern data input
- \* Canned cycle for drilling
- \* Automatic corner deceleration
- \* Coordinate system rotation
- \* Tape format for FS10/11
- \* Auxiliary function (M8-digit)
- \* Auxiliary function lock
- \* Multiple command of auxiliary function
- \* Spindle analog output
- \* Analog voltage control by PMC
- \* 1<sup>st</sup> spindle output switching function
- \* 2<sup>nd</sup> spindle output switching function
- \* Rigid tapping
- \* Tool function (T8-digit)
- \* Tool offset memory C
- \* Tool offset (G45~G48)
- \* Tool life management
- \* Tool length measurement
- \* <Editing operation>
- \* Number of registerable programs 400
- \* Program protect
- \* Extended part program editing
- \* <Setting and display>
- \* Clock function
- \* Program display
- \* Self-diagnosis function
- \* Alarm history display
- \* Operation history display
- \* Run hour and parts count display
- \* Display of spindle speed and T-code
- \* Servo setting screen
- \* Servo waveform display (Graphic module is required)
- \* Software operator's panel
- \* Data protection key

- \* Erase display
- \* Reader/puncher interface (2 ch)
- \* External tool offset
- \* External machine zero point shift
- \* External key input
- \* External work piece number search
- \* Power Mate CNC manager
- \* <Others>
- \* CNC screen display
- \* <Controlled axis>
- \* Simultaneous controllable axes; 4
- \* Axis name (X, Y, Z, U, V, W, A, B, C)
- \* Least input increment (0.001 mm, 0.001 deg, 0.001 inch)
- \* Incremental system 1/10
- \* Fine Acc & Dec control
- \* Inch/metric conversion
- \* Machine lock
- \* Overtravel
- \* Stroke limit external setting
- \* Mirror image
- \* Servo-off/mechanical handle
- \* Backlash compensation for each rapid traverse and cutting feed
- \* Stored pitch error compensation
- \* Unexpected disturbance torque detection function
- \* <Operation>
- \* DNC operation
- \* Schedule function
- \* Sequence number search
- \* Program restart
- \* Retraction for rigid tapping
- \* Dry run
- \* JOG feed
- \* Reference position return without DOG
- \* Reference position shift
- \* Manual handle feed rate
- \* Incremental feed
- \* <Interpolation functions>
- \* Linear interpolation type positioning
- \* Exact stop mode (G61)
- \* Linear interpolation (G01)
- \* <Data input/output>
- \* External I/O device control
- \* External message
- \* External data input
- \* External program input
- \* External program number search
- \* Memory card interface for maintenance
- \* Status output signal
- \* Built-in Ethernet
- \* Number of controlled axes; 4
- \* Axis control by PMC
- \* Simple synchronous control
- \* Flexible feed gear
- \* HRV control
- \* Interlock
- \* Emergency stop
- \* Stored stroke check 1
- \* Stored stroke check 2
- \* Follow-up
- \* Backlash compensation
- \* Position switch
- \* Control axis detach
- \* Automatic operation (memory)
- \* MDI operation
- \* Program number search
- \* Sequence number comparison and stop
- \* Manual intervention and return
- \* Buffer register
- \* Single block
- \* Manual reference position return
- \* Reference position setting with mechanical stopper
- \* Manual handle feed
- \* Manual handle interruption
- \* Jog and handle simultaneous mode
- \* Positioning (G00)
- \* Single direction positioning
- \* Exact stop (G09)
- \* Circular interpolation (G02/G03)

- \* Dwell (G04)
- \* Helical interpolation
- \* Skip (G31)
- \* Reference position return (G28)
- \* 2nd reference position return
- \* Normal direction control
- \* <Feed function>
- \* Rapid traverse override
- \* Feed per revolution
- \* Cutting federate clamp
- \* Rapid traverse bell shaped acceleration/deceleration
- \* Linear acceleration/deceleration after cutting feed interpolation
- \* Bell-shaped acc/dec after cutting feed interpolation
- \* Feedrate override
- \* Jog override
- \* External deceleration
- \* <Program input>
- \* Label skip
- \* Control in/out
- \* Max. programmable dimension +- 8-digit
- \* Sequence number
- \* Decimal point programming/pocket calculator type decimal point programming
- \* Input unit 10 time multiply
- \* Rotary axis designation
- \* Polar coordinate command
- \* Automatic coordinate system setting
- \* Cylindrical interpolation
- \* Threading/synchronous cutting
- \* High-speed skip
- \* Reference position return check (G27)
- \* 3rd/4th reference position return
- \* Index table indexing
- \* Rapid traverse rate; 240m/min (1 m)
- \* Feed per minute
- \* Tangential speed control
- \* Automatic acceleration/deceleration
- \* One digit F-code feed
- \* Override cancel
- \* Advanced preview control
- \* Tape cede EIA; RS244/ISO840
- \* Parity check
- \* Optional block skip
- \* Program number
- \* Absolute/incremental command
- \* Plane selection (G17, G18, G19)
- \* Rotary axis roll-over
- \* Coordinate system setting (G92)